



Fast assembly concealed hinge

- ▶ Sensys thin door hinge, door thickness from 10 mm
- ▶ Opening angle 110°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 10 - 19 mm
- ▶ Cup depth 7.8 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel, nickel plated



Drilling pattern



full overlay
(Base B 12.5 mm)

half overlay
(Base B 3 mm)

inset
(Base B -4 mm)



With integrated Silent System, with self closing feature (Sensys 8646i)

Mounting option	Mounting hole Ø x T mm	full overlay 1/50 ea.	half overlay 1/50 ea.	inset 1/50 ea.
for screwing on	-	9 094 270	9 094 280	9 094 290
with expanding sockets	Ø 10 x 8	9 094 276	9 094 286	9 094 296

Without Silent System, with self closing feature (Sensys 8646)

Mounting option	Mounting hole Ø x T mm	full overlay 1/50 ea.	half overlay 1/50 ea.	inset 1/50 ea.
for screwing on	-	9 094 360	9 094 370	9 094 380
with expanding sockets	Ø 10 x 8	9 094 366	9 094 376	9 094 386

Without Silent System, without self closing feature, for handleless applications (Sensys 8676)

Mounting option	Mounting hole Ø x T mm	full overlay 1/50 ea.	half overlay 1/50 ea.	inset 1/50 ea.
for screwing on	-	9 094 450	9 094 460	9 094 470
with expanding sockets	Ø 10 x 8	9 094 456	9 094 466	9 094 476



hettich.com/short/5480ec